

[CLAIMS]

[Claim 1] A laundry device comprising:

a cabinet having a hole;

a power cord assembly having electric wires, and a holding member at one ends of the electric wires with a groove at a circumferential surface for placing the cabinet therein, for passing through the hole, and securing to the cabinet; and

a depressed portion at a portion of the cabinet where the groove is to be placed therein, for press fitting in the groove.

[Claim 2] The laundry device as claimed in claim 1, further comprising a recess recessed toward an inner side of the cabinet compared to the other portion of the cabinet, at a portion having the hole in the cabinet formed therein

[Claim 3] The laundry device as claimed in claim 2, wherein the recess has a depth enough to prevent a rear surface of the holding member from projecting beyond the other portion of the cabinet.

[Claim 4] The laundry device as claimed in claim 1, wherein the holding member includes;

a push-in portion for being pushed into the cabinet passing through the hole, and held

at an inner side of the rearwall of the cabinet, and

a sealing portion formed as one body with the push-in portion with the groove inbetween, for being brought into close contact with an outer side of the rearwall.

[Claim 5] The laundry device as claimed in claim 4, wherein the push-in portion and the hole are rectangular.

[Claim 6] The laundry device as claimed in claim 1, wherein the groove has a width greater than a thickness of the cabinet.

[Claim 7] The laundry device as claimed in claim 1, wherein the depressed portion has a step toward an inner or outer side of the cabinet.

[Claim 8] The laundry device as claimed in claim 1, wherein the holding member is formed of an elastic material.

[Claim 9] The laundry device as claimed in claim 1, wherein the depressed portion further includes at least one holding portion.

[Claim 10] The laundry device as claimed in claim 9, wherein the holding portion is

projected toward the inner side of the cabinet.

[Claim 11] A laundry device comprising:

a cabinet having a hole;

a power cord assembly having electric wires, and a holding member at one ends of the electric wires with a groove at a circumferential surface for placing the cabinet therein, for passing through the hole, and securing to the cabinet; and

at least holding portion projected from a portion of the cabinet where the groove is to be placed therein to an inner or outer side of the cabinet.

[Claim 12] The laundry device as claimed in claim 11, further comprising a recess recessed toward an inner side of the cabinet compared to the other portion of the cabinet, at a portion having the hole in the cabinet formed therein

[Claim 13] The laundry device as claimed in claim 12, wherein the recess has a depth enough to prevent a rear surface of the holding member from projecting beyond the other portion of the cabinet.

[Claim 14] The laundry device as claimed in claim 11, wherein the holding member includes;

a push-in portion for being pushed into the cabinet passing through the hole, and held at an inner side of the rearwall of the cabinet, and

a sealing portion formed as one body with the push-in portion with the groove inbetween, for being brought into close contact with an outer side of the rearwall.

[Claim 15] The laundry device as claimed in claim 14, wherein the push-in portion and the hole are rectangular.

[Claim 16] The laundry device as claimed in claim 14, wherein the holding member is formed of an elastic material.

[Claim 17] The laundry device as claimed in claim 11, wherein the groove has a width greater than a thickness of the cabinet.

[Claim 18] The laundry device as claimed in claim 11, wherein the holding portion includes a portion of the portion where the groove is to be placed therein cut, and bent at a tip of the cut toward the inner or outer side of the cabinet by a predetermined angle to slope the tip.

[Claim 19] The laundry device as claimed in claim 18, wherein there are a plurality

of holding portions, and the holding portions are projected in the same direction.

[Claim 20] The laundry device as claimed in claim 19, wherein the tips of adjacent holding portions are projected in directions opposite to each other.

[Claim 21] The laundry device as claimed in claim 18, wherein there are a plurality of holding portions, and some of the holding portions are projected in a direction opposite to a direction rest of the holding projections are projected.